

Nikon DTM-362/NPL-362 Total Station

The hardworking total station solution from Nikon

The Nikon 362 Total Station offers the superior optics, intelligent design, and quality components your surveying jobs demand. Add the powerful Nikon onboard software, and you have a total station solution that performs all day, every day.

3" accuracy

For most construction and surveying applications, the Nikon 362 Total Station's superior 3" accuracy is ideal. And with its quality Nikon construction and reliability, you can be confident that you will achieve this accuracy with every measurement.

Rugged and reliable

The Nikon 362 Series robust construction and long battery life enable it to work as long and as hard as you do. On a single battery, the Nikon DTM-362 provides nonstop distance/angle measurement of 16 hours, or 27 hours of measurements spaced 30 seconds apart. And with its tough water-resistance rating of IPX6, both Nikon 362 models will keep on working whatever the weather.

Easy to use

The Nikon 362 Total Station's onboard software is powerful, but is also intuitive and easy to use. Accessed by a full alphanumeric keyboard and large configurable display, the software makes data management fast and simple. Perform surveying tasks quickly and efficiently, and



gain even further productivity as you learn to maximize the total station's capabilities.

Reflectorless EDM for safety and increased productivity

Gain complete confidence in your measurements with Nikon NPL-362 reflectorless technology.

This completely eye-safe (Class 1) reflectorless system uses a patented focused beam design to provide positive target identification, and an excellent combination of range and accuracy (up to 200 m/650 ft away). It automatically rejects erratic return signals that are reflected from objects that are out of focus. Simply focus

the circular reticle on the target and measure. This unique feature measures to difficult and dangerous locations with confidence.



KEY FEATURES

- 3" accuracy
- Rugged and reliable
- Easy to use
- Powerful onboard software

Nikon

Nikon DTM-362/NPL-362 Total Station

NPL-362

Telescope

Magnification **26×** (16×/32× with optional eyepieces)
Effective diameter of objective 40 mm (1.57 in)
EDM: 50 mm (1.97 in)

Field of view 1°30'
Resolving power 3"
Minimum focusing distance 1.6 m (5.3 ft)

Distance measurement

Reflectorless mode (white target)² **1.6 m to 200 m** (5.3 ft to 650 ft)
Range with Nikon specified prisms

Normal conditions³

With reflector sheet (5 × 5 cm) 1.6 m to 300 m (5.3 ft to 980 ft)
With single prism 1.6 m to 5,000 m (5.3 ft to 16,400 ft)

Good conditions⁴

With reflector sheet (5 × 5 cm) 1.6 m to 300 m (5.3 ft to 980 ft)
With single prism **1.6 m to 5,000 m** (5.3 ft to 16,400 ft)

Accuracy (Prism/Precise mode) ±(3+2 ppm × D) mm
..... ±(3+3 ppm × D) mm
..... (-20 °C to -10 °C, +40 °C to +50 °C)
..... ±5 mm: 1.6 m to 5/10 m
..... (5.3 ft to 17.4/32.8 ft) for reflector sheets/prisms

Accuracy (Reflectorless/Precise mode)

..... ±(5+2 ppm × D) mm
..... (5+3 ppm × D) mm
..... (-20 °C to -10 °C, +40 °C to +50 °C)

Measuring interval⁵

Prism mode

Precise mode 1.6 sec. (initial 2.6 sec.)
Normal mode 0.5 sec. (initial 2.2 sec.)

Reflectorless mode

Precise mode 1.6 sec. (initial 3.5 sec.)
Normal mode 0.8 sec. (initial 3.2 sec.)

Least count

Precise mode 1 mm (0.002 ft)
Normal mode 10 mm (0.02 ft)

Weight (approx.)

Main unit (with battery) 5.5 kg (12.1 lb)

On-board Ni-MH battery BC-65

Operation time¹

Continuous distance/angle measurement Approx. 6.5 hours
(Reflectorless mode: 7 hours)

Distance/angle measurement every 30 seconds Approx. 15 hours
(Reflectorless mode: 16 hours)

Angle measurement Approx. 27 hours
(Prism and Reflectorless modes)

Quick charger Q-75U/E Approx. 2.0 hours for full recharge

Dimensions (W × D × H) 168 mm × 173 mm × 347 mm
(6.6 in × 6.8 in × 13.7 in)

¹ Battery life specification at 25 °C. Operation time may be shorter if battery is not new.

² White objects with high reflectivity. Measuring distance may vary depending on targets and measuring conditions.

³ Ordinary haze, visibility approx. 20 km/12.5 miles.

⁴ No haze, visibility over 40 km/25 miles.

⁵ Measuring time may vary depending on measuring distance and conditions.

DTM-362

Telescope

Magnification 33× (21×/41× with optional eyepieces)
Effective diameter of objective 45 mm (1.77 in)
EDM: 50 mm (1.97 in)

Field of view 1°20'
Resolving power 2.5"
Minimum focusing distance 1.3 m (4.26 ft)

Distance measurement

Range with Nikon specified prisms

Normal conditions³

With reflector sheet (5 × 5 cm) 5 m to 100 m (16.4 ft to 328 ft)
With single prism 2,000 m (6,560 ft)
With triple prism 2,600 m (8,530 ft)

Good conditions⁴

With reflector sheet (5 × 5 cm) 5 m to 100 m (16.4 ft to 328 ft)
With single prism 2,300 m (7,540 ft)
With triple prism 3,000 m (9,840 ft)

Accuracy (Prism/Precise mode) ±(3+2 ppm × D) mm
..... ±(3+3 ppm × D) mm
..... (-20 °C to -10 °C, +40 °C to +50 °C)

Measuring interval⁵

Prism mode

Precise mode 1.6 sec. (initial 1.6 sec.)
Normal mode 1.0 sec. (initial 1.4 sec.)

Least count

Precise mode 1 mm (0.002 ft)
Normal mode 10 mm (0.02 ft)

Weight (approx.)

Main unit (with battery) 5.3 kg (11.7 lb)

On-board Ni-MH battery BC-65

Operation time¹

Continuous distance/angle measurement Approx. 16 hours

Distance/angle measurement every 30 seconds Approx. 27 hours

Angle measurement Approx. 30 hours

Quick charger Q-75U/E Approx. 2.0 hours for full recharge

Dimensions (W × D × H) 168 mm × 173 mm × 335 mm
(6.6 in × 6.8 in × 13.2 in)

Shared Specifications

Ambient temperature range -20 °C to +50 °C (-4 °F to +122 °F)

Atmospheric correction

Temperature range -40 °C to +60 °C (-40 °F to +140 °F)

Barometric pressure 400 mmHg to 999 mmHg/533 hPa to
1,332 hPa/15.8 inHg to 39.3 inHg

Angle measurement

Horizontal angle Diametrical

Vertical angle Single

Minimum increment (Degree, Gon, MIL6400) Degree: 1/5/10"

Gon: 0.2/1/2 mgon

MIL6400: 0.005/0.02/0.05 mil

DIN 18723 accuracy (horizontal and vertical) 3"/1 mgon

Tilt sensor

Type Dual-axis

Compensation range ±3'

Setting accuracy 1"

Level vial

Plate level vial 30"/2 mm

Circular level vial 10"/2 mm

Optical plummet

Magnification 3×

Display Both sides, graphic LCD (128 × 64 dot)

Point memory 10,000 records

Specifications and equipment are subject to change without any notice or obligation on the part of the manufacturer.

NORTH AMERICA

Tripod Data Systems

P O Box 947 • Corvallis, OR 97339 • USA

+1-541-753-9322 Phone • +1-541-757-7439 Fax

www.tdsway.com

EUROPE

Trimble GmbH

Am Prime Parc 11 • 65479 Raunheim • GERMANY

+49-6142-2100-0 Phone

+49-6142-2100-550 Fax

ASIA-PACIFIC

Trimble Navigation Singapore PTE Limited

80 Marine Parade Road • #22-06, Parkway Parade

Singapore 449269 • SINGAPORE

+65-6348-2212 Phone • +65-6348-2232 Fax

YOUR LOCAL NIKON OFFICE OR REPRESENTATIVE

Nikon